

Varenummer	100.42. – 3000K
Varenummer	100.42. – 4000K
Beskrivelse	60*60 LED panel til skinnesystem
Volt	200-240 V~
URG	<19
Mac Adams	<3, Garanteres under hele levetiden
Watt	36W
Spredning	120°
Hz	50/60Hz
Starts strøm	36Watt
mA pr.armatur	0.3mA
Flicker	2%=<
Dæmpbar	Non dim / 1-10V / Push dim / Dali dim
Spredning	120°
RA	> 85
Farvetemperatur	Vælg mellem 3000K/4000K
Lumen	3950Lm
Levetid	100.000 timer
L80/B20	>100000 at Ta=25°
Isoleringsklasse	Klasse III
Energiklasse	A++
Materiale	Aluminium / splinter fri polykarbonat
Anvendelse	Indendørs / hygiejniske faciliteter.
IP	44-21
Størrelse	Mål: 595*595*12mm Ydre mål: 615*615mm
Vedligeholde	Kan rengøres med klud (hårdt opvredet klud) -eller støvkost.
Yderlige data	Panelet må monteres i brandbart materialer/ isolering, men med 1-2cm luft på bagsiden op til isolerings materialer samme er gældende omkring driverhus.
Garanti	5års produkt garanti



Isolering 50mm fra driver



indbygningshøjde på panel og driver er 52mm

Udskæringsmål 595x595mm

